



588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China  
 Telephone: +86 (0) 21 6191 5666  
 Fax: +86 (0) 21 6191 5678  
 ee.shanghai@sgs.com

Report No.: SHEM180700553903  
 Page: 1 of 7

## 1 Cover Page

# ***RF Exposure Evaluation Report***

<b>Application No.:</b>	SHEM1807005539CR
<b>Applicant:</b>	ZIMI CORPORATION
<b>Equipment Under Test (EUT):</b>	
<b>NOTE:</b> The following sample(s) was/were submitted and identified by the client as	
<b>Product Name:</b>	Mi Wireless Charging Pad
<b>Model No.(EUT):</b>	WPC01ZM
<b>Trade mark:</b>	MI
<b>Standards:</b>	EN 62311:2008
<b>Date of Receipt:</b>	2018-07-10
<b>Date of Test:</b>	2018-07-19 to 2018-07-23
<b>Date of Issue:</b>	2018-08-17
<b>Test Result:</b>	<b>Pass*</b>

\* In the configuration tested, the EUT detailed in this report complied with the standards specified above

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EU Declaration of conformity and compliance with all relevant EU Directives.





Parlam Zhan  
 E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record			
Version	Description	Date	Remark
00	Original	2018-08-17	/

<b>Authorized for issue by:</b>			
			
		<hr/>	
		<b>Vincent Zhu /Project Engineer</b>	
			
		<hr/>	
		<b>Parlam Zhan / Reviewer</b>	



## 2 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 CONTENTS .....</b>	<b>3</b>
<b>3 GENERAL INFORMATION.....</b>	<b>4</b>
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF E.U.T.....	4
3.3 TEST LOCATION.....	5
3.4 TEST FACILITY .....	5
<b>4 TEST STANDARDS AND LIMITS .....</b>	<b>6</b>
<b>5 CALCULATION FORMULA AND TEST RESULT .....</b>	<b>7</b>
5.1 CALCULATION FORMULA.....	7
5.2 TEST RESULTS .....	7



### 3 General Information

#### 3.1 Client Information

Applicant:	ZIMI CORPORATION
Address of Applicant:	Room A913, No.159 Chengjiang Road, Jiangyin City, Jiangsu Province, 214431, P.R.C
Manufacturer:	ZIMI CORPORATION
Address of Manufacturer:	Room A913, No.159 Chengjiang Road, Jiangyin City, Jiangsu Province, 214431, P.R.C

#### 3.2 General Description of E.U.T.

Power supply:	DC 5V by USB Port
Cable:	DC Cable 1m for USB Port
Internal source:	40MHz

### 3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

No tests were sub-contracted.

### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **NVLAP (Certificate No. 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). Certificate No. 201034-0.

- **FCC –Designation Number: CN5033**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

## 4 Test Standards and Limits

The evaluation has been performed on the EUT, pursuant to the relevant requirements of the following document(s) and the harmonized EN standard(s) covering essential requirements under article 3.1a of the RED Directive (2014/53/EU).

Identity	Document Title	Version
Council Recommendation of 12 July 1999(1999/519/EC)	On the limitation of exposure of the general public to electromagnetic fields (0Hz to 300GHz)	1999
EN 62311	Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz – 300 GHz)	2008

**Limit:** According to EN 62311, the criteria listed in the below table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified table 2 of Council Recommendation 1999/519/EC.

Table 2  
Reference levels for electric, magnetic and electromagnetic fields  
(0 Hz to 300 GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field ( $\mu$ T)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )
0-1 Hz	—	$3,2 \times 10^4$	$4 \times 10^4$	—
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—
8-25 Hz	10 000	$4 000/f$	$5 000/f$	—
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—
0,8-3 kHz	$250/f$	5	6,25	—
3-150 kHz	87	5	6,25	—
0,15-1 MHz	87	$0,73/f$	$0,92/f$	—
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

### Notes

- $f$  as indicated in the frequency range column.
- For frequencies between 100 kHz and 10 GHz,  $S_{eq}$ ,  $E^2$ ,  $H^2$ , and  $B^2$  are to be averaged over any six-minute period.
- For frequencies exceeding 10 GHz,  $S_{eq}$ ,  $E^2$ ,  $H^2$ , and  $B^2$  are to be averaged over any  $68/f^{1.05}$ -minute period ( $f$  in GHz).
- No E-field value is provided for frequencies < 1 Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 25 kV/m. Spark discharges causing stress or annoyance should be avoided.

## 5 Calculation Formula and Test Result

### 5.1 Calculation Formula

$$Pd = (P_{out} * G) / 4\pi R^2$$

Where:

Pd = Power density in W/m<sup>2</sup>

P<sub>out</sub> = Output power to antenna in W

G = Antenna Gain in linear scale

π = 3.14

R = distance to the center of radiation of antenna (in meter) = 0.2m

**NOTE:** Pd limit = 10W/m<sup>2</sup>.

### 5.2 Test Results

Refer to the test report SHEM180700553902, the measured maximum Magnetic Fields is 15.51 dBuA/m.

The limit is converted from EIRP in watts to magnetic field strength in dB (uA/m) using the following formula:

$$H_{lim} = 20 \times \log_{10} \left( \frac{\sqrt{P_{lim} / 30}}{4\pi d} \right) + 120$$

where

$H_{lim}$  = magnetic field strength limit, in dB(μA/m)

$P_{lim}$  = EIRP limit, in Watts

$d$  = measurement distance, in metres

$$\text{So, } P = ((10^{(15.51 - 120)/20}) * 4 \pi * 3)^2 * 30 = 1.14 * 10^{-8} \text{W}$$

The H-field of the EUT is below the max permitted sending level, and then the EUT is not need to conduct SAR measurement.

**--The End of Report--**